



- A Genuine 100% Instant Hot Peel Film Which Works On Every Design
- The Highest Ink Absorption Of Any DTF Film On The Market, Providing The Highest Quality Transfers
- Clean Printing Of Minute Designs And Letters
- No Ghosting Or Ink Left On The Film
- Matt Coating Ensures No Film Slippage Or Wander Through The DTF Machine, Or On Wind Up
- Heat Stabilised PET, To Ensure There Is No Shrinkage Of Your Image Design After The Printing Process
- No Residue Left On The Surface Of Transfers Or Garment After Heat Pressing
- Also Suitable For Warm Or Cold Peel
- Save Money On Ink Costs, Hotmelt Powder And Energy With The Efficient And Consistent Coating Technology
- Apply Transfers As Low As 120 Degrees Centigrade
- A Lower (75 Degrees Centigrade) Oven Temperature Is Possible

| | |
|----------------------|---|
| Application Pressure | Medium Even Pressure |
| Pressing Guideline | 140 to 150 Degrees C for 8 to 10 Secs. Larger Transfers as Low as 120 Degrees C x 10 Secs |
| Suitable Fabric | Cotton, Polyester, Mixtures of Polyester And Cotton, Acrylic, Nylon, Treated Leather And More |
| Peel | Instant Hot Peel. Also suitable for warm or cold peel if required |
| Accreditation | EN71-3:2019, CPSIA, OEKOTEX 100, Control Union Certified Recycled Blended Polyester |



Allow 24 Hours After Application Before Washing

 MATERIAL
DTF Film Matt Coated

 SIZE
100M

 CARTON
1

 ORIGIN HS CODE
South Korea 3920629090

| | |
|-------------|-------|
| Sizes | 100m |
| Width (cm) | 60 |
| Length (cm) | 10000 |

Measurements Are Approximate. Manufacturer Tolerances Apply.

MATT
DTFM